

IMR EX610 SMART SENSOR GAS DETECTOR**MAIN FUNCTION AND FEATURES**

- SMART sensor module, easy for replacement and maintenance
- Intrinsically safe design
- Wide screen LCD with backlighting
- High / Low alarm adjustable
- Calibration level adjustable for each calibration
- Combustible gas channel with high-concentration protection function
- Low-voltage alert
- Internal memory storage of measurements (10,000 records)
- Data upload to PC
- Audible, visual and vibration alarm
- Self-test power on
- Self-diagnostic and self-correction function

IMR EX610 TECH SPECIFICATIONS

- Target gas: combustible gas, toxic gas, Oxygen
- Detecting method: Natural diffusion
- Response Time:
Semi-conductor, Catalytic, Thermal Conductivity $t_{90} < 30s$
Oxygen, Carbon Monoxide, Hydrogen Sulfide $t_{90} < 30s$
Other Sensors $t_{90} < 120s$
- Working Conditions:
Combustible Gas: $-40^{\circ}C \sim 70^{\circ}C$
Toxic Gas: $-20^{\circ}C \sim 50^{\circ}C$
Working humidity $\leq 95\%RH$ non-condensating
- Power Source: Lithium battery (DC3.7V 1800mAh)
- Charging time: 4 ~ 6hours
- Continuous working time:
 ≥ 8 hours (for combustible gas and toxic gas)
 ≥ 300 hours (for toxic gas under temperature of $20^{\circ}C$)
- USB connectivity for data transfer
- Explosion-proof grade: Exia II CT4
- Ingress protection: IP66
- Dimensions: 108.4mm x 61mm x 36mm
- Weight: about 191g



IMR EX610 SMART Sensor gas detector

IMR EX610 ACCESSORIES

FLEXIBE GAS PROBE

Used to collect gas samples in confined areas

Telescoping probe

Collection tube

Item# EX660-Gas Probe



PUMP

Use to collect gas samples in confined spaces

Calibration

Item#: IX176-Pump



Gas	Detection	L-Alarm	H-Alarm	TWA (ppm)	STEL (ppm)
C3H8	0-100% LEL	20% LEL	50% LEL	N/A	N/A
O2	0-30% vol.	19.5% vol.	23.5% vol.	N/A	N/A
H2S	0-100 ppm	10 ppm	15 ppm	10 ppm	15 ppm
CO	0-1000 ppm	35 ppm	200 ppm	35 ppm	200 ppm
CO	0-2000 ppm	35 ppm	200 ppm	35 ppm	200 ppm
NH3	0-100 ppm	25 ppm	50 ppm	25 ppm	35 ppm
CL2	0-20 ppm	5 ppm	10 ppm	0.5 ppm	1.0 ppm
SO2	0-100 ppm	2 ppm	5 ppm	2 ppm	5 ppm
CO2	0-5000 ppm	1500 ppm	2000 ppm	N/A	N/A
CH4	0-5% vol.	0.5% vol.	1% vol.	N/A	N/A
H2	0-100% LEL	20% LEL	50% LEL	N/A	N/A
H2	0-1000 ppm	35 ppm	250 ppm	N/A	N/A
NO	0-100 ppm	25 ppm	50 ppm	25 ppm	50 ppm
NO2	0-20 ppm	5 ppm	10 ppm	5 ppm	10 ppm
PID	0-100 ppm	PID Sensor Module for VOC			
PH3	0-20 ppm	5 ppm	10 ppm	5 ppm	10 ppm
HCN	0-100 ppm	5 ppm	10 ppm	5 ppm	10 ppm
HCI	0-20 ppm	5 ppm	10 ppm	5 ppm	10 ppm